



Technical Specifications

Dimensions WxHxD:	545 x 600 x 203 mm
Weight:	28 kg
Housing material:	sheet steel, powder-coated, ASA, PC
Colour:	similar to RAL 9006
Operating temperature:	+5...+50 °C
Relative humidity:	5...95 %, non-condensing
Power requirement:	110...240 VAC
keyTag frequency:	125 kHz
Backup battery:	12 VDC / 2,3 Ah
Digital output:	4x 30 VDC / 1A for up to 16 alarms
Certifications:	CE

Product Description

The maxx 6U cabinet is a compact key management system with an elegant design. Its high quality mix of materials make it ideal to be installed in a foyer where design matters. On the other hand, the automatic roller shutter requires much less space compared to an ordinary door which makes access to the cabinet easier in locations with limited space, e.g., a narrow corridor.

Furthermore, the automatic rollers shutter prevents human error since it will automatically close after a certain time so that the cabinet cannot accidentally be left open.

The maxx 6U offers space for 2 panels which provides flexibility to equip the maxx with the panels to meet your needs.

Features

- Zero-maintenance RFID technology
- Compact and elegant design
- Automatic roller shutter
- Flexible, modular design with 2 positions for panels
- Emergency opening in case of power failure
- Standalone mode in case of network errors

Product family

proxSafe® is the intelligent management system for keys and equipment with comprehensive auditing and reporting features. Control who has access to specific keys or equipment and when they can be used and by whom. Keys, radios, test equipment, tools, laptops, and much more can now be managed efficiently and traceably, so that you always know where they are – fully automatically and electronically documented.



Find an overview of all associated proxSafe® products here: <https://go.deister.com/kmen>



For access to our specification libraries visit: <http://go.deister.com/ab78>

Dimensions

All measurements in mm.

